

# Polyflo<sup>®</sup> 20



## Product Data

Property	Test Method	Specifications
Specific Gravity, @ 60°F	ASTM D 1298	1.041 – 1.055
Viscosity, @ 40°C	ASTM D 445	25.0 – 29.0
Flash Point, °F	ASTM D 92	280 minimum
Mixed Aniline Point, °C	ASTM D 611	32.0 maximum

### Description

Polyflo<sup>®</sup> 20 is a C11-C30 aromatic mixture of hydrocarbons used as a secondary plasticizer and extender oil in flexible PVC, polyurethane elastomers, rubber and epoxies.

### Shipping Information

Polyflo<sup>®</sup> 20 is available in rails cars (180,000 lbs net weight), trucks (45,000 lbs net weight), tote (2,300 lbs net weight), and drum (470 lbs net weight).

### Safety and Handling Information

For specific information on the safe handling of this product, please, refer to the material safety data sheet. Copies are available upon request.

### For Additional Information, please contact:



CHEM Group, LLC.  
2406 Lynch Road  
Evansville, IN 47711  
(800) 489-2306

### Disclaimer

Polyflo<sup>®</sup> is a registered trademark of CHEM Group, LLC. The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of CHEM Group and its subsidiaries. It is the responsibility of the user to comply with applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation or use any of the herein materials or processes in violation of existing or future patent.